



**SOLIDEAL**

# **SOLIDEAL**®

## **RESILIENT SOLIDS**

**RESILIENT**

- Solideal resilient solids are a true value for the money
- Three stage construction absorbs shocks and gives maximum comfort to the driver
- The natural rubber compounds reduce heat build-up and increase chunk and tear resistance which gives a longer trouble free life
- The deep lug tread pattern means greater traction and bigger footprint



[solideal.com](http://solideal.com)

# SOLIDEAL®

## RESILIENT SOLIDS

## RESILIENT



Size	Rim Width	Tread	OD (in.)	Section Width (in.)	Load Cap. Load - 6 mph (lbs.)	Weight (lbs.)
4.00 - 4	2.1	MIL	12	5	1069	15
4.00 - 4	2.5	MIL	12	5	1069	15
4.00 - 8	2.5	HT	16	5	1896	28
4.00 - 8	2.5	RIB	16	5	1896	28
4.00 - 8	3	HT	16	5	1896	30
4.00 - 8	3	RIB	16	5	1896	30
4.00 - 8	3.25	HT	16	5	1896	30
4.00 - 8	3.75	RIB	16	5	2017	30
5.00 - 8	3	HT	18	6	2833	44
5.00 - 8	3.25	HT	18	6	2833	36
5.00 - 8	3.75	RIB	18	6	3009	51
6.00 - 9	4	RIB	21	7	3770	71
6.00 - 9	4	HT	21	7	3770	67
6.50 - 10	5	HT	23	8	4685	90
6.50 - 10	5.5	HT	23	8	4685	89
7.50 - 10	5	HT	25	9	6140	117
7.50 - 10	5	HT	25	9	6140	117
7.50 - 10	5.5	HT	25	9	6140	119
7.00 - 12	5	HT	26	8	5831	110
5.50 - 15	4.5	HT	26	6	4861	84
7.00 - 15	5.5	HT	29	8	7088	139
7.00 - 15	6	HT	29	8	7088	150
7.50 - 15 (30)	5.5	HT	30	9	7804	180
7.50 - 15 (30)	6	HT	30	9	7804	180
7.50 - 15 (30)	6.5	HT	30	9	7804	180
28 x 9 - 15	7	HT	27	9	6889	145
8.25 - 15	5.5	HT	32	10	9204	220
8.25 - 15	6.5	HT	32	10	9480	220
6.50 - 16	5.5	HT	29	8	5203	169
7.50 - 16	5.5	HT	31	9	7937	195
7.50 - 16	5.5	SKS	31	9	7937	195
7.50 - 16	6	HT	31	9	7937	195
7.50 - 16	6	SKS	31	9	7937	195

Size	Rim Width	Tread	OD (in.)	Section Width (in.)	Load Cap. Load - 6 mph (lbs.)	Weight (lbs.)
8.00 - 16	5.5	SKS	32	9	8322	195
9.00 - 20	6.5	HT	39	11	10692	331
9.00 - 20	7	HT	39	11	10692	331
9.00 - 20	7.5	HT	39	11	10692	331
10.00 - 20	7	HT	41	11	12015	412
10.00 - 20	7	SM	41	11	12015	433
10.00 - 20	7.5	HT	41	12	12015	412
10.00 - 20	7.5	SM	41	12	12015	433
10.00 - 20	8	HT	41	12	12015	412
10.00 - 20	8	SM	41	12	12015	433
12.00 - 20	8	HT	43	13	15024	455
12.00 - 20	8	SM	43	13	15024	470
12.00 - 20	8.5	HT	43	13	15024	480
12.00 - 20	8.5	SM	43	13	15024	490
12.00 - 20	10	SM	43	14	17064	521
14.00 - 24	10	HT	52	16	22046	800
15 x 4 1/2 - 8	3	HT	15	5	2072	29
16 x 6 - 8	4.33	HT	16	6	2987	44
18 x 7 - 8	4.33	HT	18	7	4288	51
18 x 9 - 8	7	HT	18	9	5071	68
16 x 5 - 9	4	RIB	16	5	2094	60
21 x 8 - 9	6	HT	21	9	5523	87
23 x 9 - 10	6.5	HT	23	10	6889	110
200 / 50 - 10	6.5	HT	18	8	4938	55
23 x 10 - 12	8	HT	23	11	7540	108
27 x 10 - 12	8	HT	27	11	7804	150
250 - 15	7	HT	28	10	9259	145
250 - 15	7.5	HT	28	10	9259	145
300 - 15	8	HT	32	13	11706	235
28 x 12.5 - 15	9.75	HT	27	14	10086	205
355 / 65 - 15	9.75	HT	32	14	14176	285
355 / 85 - 24	12	SM	48	13	23545	820

Distributed by:



**SOLIDEAL®**